

Product Code	Thermal Storage Capacity			Dimensions (mm)				Pipe Sizing (mm)			Connection Size	
	Whh @ 55°C	V ₅₀ (Ltrs @ 55°C)	V ₆₀ (Ltrs @ 60°C)	Width	Depth	Height	Weight Kg	Heating	Domestic Cold Water	Domestic Hot Water	Heating	Hot & Cold Water
eS5-HW-U	6	90	109	455	595	595	103	28	22	22	1" BSP	3/4" BSP
eS10-HW-U	10	185	218	455	595	510	154	28	22	22	1" BSP	3/4" BSP
eS12-HW-U	12	285	302	455	595	1200	192	28	22	22	1" BSP	3/4" BSP

Product Code	Connected Electrical Load @ 230V - 50hz (W)	Power Supply	Working Pressures (Bar)		Recommended Flow Rate (Ltrs)		Hot Water Temperature Range °C	Heat Source Flow Temp °C		Heat Loss Rate kWh/24	Energy Efficiency Rating
			Min	Max	Min	Max		Min	Max		
eS5-HW-U	2800	1PH / 230V	1.5	10	2	10	45-60	55	80	0.65	A+
eS10-HW-U	2800	1PH / 230V	1.5	10	2	15	45-60	55	80	0.74	A+
eS12-HW-U	2800	1PH / 230V	1.5	10	2	20	45-60	55	80	0.83	A+

Product Code	Application	Compatibility (Primary Heat / Energy Source)									
		Boiler	Low Temp ASHP	High Temp ASHP	GSHP	Solar PV	Solar Thermal	Mains Electric	Off Peak Tariff Capability	Emergency Electric Back Up	Smart / Wi-Fi Enabled
eS5-HW-U	Hot Water	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
eS10-HW-U	Hot Water	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
eS12-HW-U	Hot Water	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y